



HLCV.EX27677 Strainers, Pipeline

[Page Bottom](#)

Strainers, Pipeline

[See General Information for Strainers, Pipeline](#)

AFCO (AMERICAN FIRE PRODUCTS COMPANY) CO

EX27677

500 DELAWARE AVE, STE 1 #1960
WILMINGTON, DE 19899 USA

Strainers, Y- type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 300 psi or 2070 kPa, Model(s) SR01-300-FF, SR01-300-GG

NOTE - Loss of head will approximate 7.22 psi (49.78 kpa) for the 2 in. size at 157.63 GPM, 5.89 psi (40.61 kpa) for the 2-1/2 in. size at 224.86 GPM, 8.24 psi (56.81 kpa) for the 3 in. size at 347.53 GPM, 5.88 psi (40.54 kpa) for the 4 in. size at 598.54 GPM, 7.63 psi (52.61 kpa) for the 5 in. size at 940.7 GPM, 4.82 psi (33.23 kpa) for the 6 in. size at 1358.85 GPM, 5.83 psi (40.20 kpa) for the 8 in. size at 2405.84 GPM, 7.25 psi (49.99 kpa) for the 10 in. size at 3795.17 GPM and 5.73 psi (39.51 kpa) for the 12 in. size at 5442.11 GPM.

[Last Updated](#) on 2017-12-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".

